



WARRIOR® ROOFING MANUFACTURING

3050 WARRIOR ROAD • TUSCALOOSA, AL 35404 • PHONE (205) 553-1734 • FAX (205) 553-1755
323 DEVELOPMENT AVENUE • CHAMBERSBURG, PA 17201 • PHONE (717) 709-0323 • FAX (717) 709-0027

SPECIFICATIONS

#15 ASTM

Our #15 ASTM asphalt saturated organic felt is manufactured to meet or exceed the following:

ASTM – D226, Type I and as a prepared roofing accessory classified by U.L. Laboratories as to external fire exposure only.

Dimensions and specifications of #15 ASTM are:

Width of roll:	36" +/- .7%
Area:	432 sq. ft.
Net mass of saturated felt:	11.5 lbs./100 sq. ft.
Net mass of saturant:	6.2lbs./100 sq. ft.
Saturant weight:	Shall not be less than 1.2 times the weight of the moisture free felt
Packaging:	The rolls are palletized and wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.

IMPORTANT: Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval code # is FL 2346.

THIS PRODUCT IS WATER RESISTANT. IT IS NOT WATERPROOF.

Updated July 5, 2022