



WARRIOR® ROOFING MANUFACTURING

3050 WARRIOR ROAD • TUSCALOOSA, AL 35404 • PHONE (205) 553-1734 • FAX (205) 553-1755
323 DEVELOPMENT AVENUE • CHAMBERSBURG, PA 17201 • PHONE (717) 709-0323 • FAX (717) 709-0027

SPECIFICATIONS

#30 ASTM

Our #30 ASTM asphalt saturated organic felt is manufactured to meet or exceed the following:

ASTM – D226, Type II – Commonly called No. 30 Asphalt Felt
FED SPECIFICATION – HHR – 595B, TYPE 30
U.L. Standard 55A for Type 30 asphalt saturated underlayment

Dimensions and specifications of #30 ASTM are:

| | |
|------------------------------------|--|
| Width of roll: | 36" +/- .7% |
| Area: | 216 sq. ft. |
| Net mass of saturated felt: | 26.0 lbs./100 sq. ft. |
| Net mass of saturant: | 15.0 lbs./100 sq. ft. |
| Saturant weight: | Shall not be less than 1.5 times the weight of the moisture free felt |
| Packaging: | The rolls are palletized and wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels. |

IMPORTANT: Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval code # is FL 2346. Per Florida Building Code 1517.4.1 this product is marked with a yellow line signifying compliance with the High Velocity Hurricane Zone requirements.

THIS PRODUCT IS WATER RESISTANT. IT IS NOT WATERPROOF.

Updated July 5, 2022