



# **WARRIOR® ROOFING MANUFACTURING**

---

3050 WARRIOR ROAD • TUSCALOOSA, AL 35404 • PHONE (205) 553-1734 • FAX (205) 553-1755  
323 DEVELOPMENT AVENUE • CHAMBERSBURG, PA 17201 • PHONE (717) 709-0323 • FAX (717) 709-0027

## SPECIFICATIONS

### **30w**

Our 30w asphalt saturated organic felt is manufactured to meet or exceed the following:

ASTM – D4869, Type II

Dimensions and specifications of 30w are:

<b>Width of roll:</b>	36" +/- .7%
<b>Area:</b>	216 sq. ft.
<b>Net mass of saturated felt:</b>	13.0 lbs./100 sq. ft.
<b>Net mass of saturant:</b>	6.0 lbs./100 sq. ft.
<b>Saturant weight:</b>	Shall not be less than 1.2 times the weight of the moisture free felt
<b>Packaging:</b>	The rolls are palletized and wrapped securely and the manufacturer's or distributor's name, type, and specification markings are evident on the label. UPC bar coding is included on all our labels.

**IMPORTANT:** Warrior Roofing Manufacturing is a statewide approved vendor for the State of Florida. The Florida Product Approval code # is FL 2346.

**THIS PRODUCT IS WATER RESISTANT. IT IS NOT WATERPROOF.**

Updated July 5, 2022