

# WARRIOR® ROOFING MANUFACTURING

3050 WARRIOR ROAD • TUSCALOOSA, AL 35404 • PHONE (205) 553-1734 • FAX (205) 553-1755

323 DEVELOPMENT AVENUE • CHAMBERSBURG, PA 17201 • PHONE (717) 709-0323 • FAX (717) 709-0027

# SAFETY DATA SHEET

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name: Chemical Family: Formula:	Asphalt Saturated Organic Roofing Underlayment Asphalt and Organic Felt Mixture
Product Use:	Secondary Water Barrier
Product Name(s):	15w, 30w, #15ASTM, #30ASTM, #15 Plain, #30 Plain, #15 Felt, #30 Felt, 18" Split, #15 Perforated 15NR, 30NR
Manufacturer:	Warrior Roofing Manufacturing 3050 Warrior Road Tuscaloosa, AL 35404

### Health and Technical Contacts:

Health Issue Info (8:00 AM - 5:00 PM US Central Time) 800-749-3358 Technical Product Info (8:00 AM - 5:00 PM US Central Time) 800-749-3358

### **Emergency Contact:**

CHEMTREC (24 Hours Daily) 800-424-9300

#### **SECTION 2 - HAZARDS IDENTIFICATION**

**Emergency Overview:** Under normal use conditions and when handled as

	intended, the products covered in this SDS are not expected to pose a health risk or physical hazard to humans.
Potential Health Effects:	
Inhalation:	One should avoid high levels of dust (levels in excess of OSHA PEL or if irritation occurs). In the event of a high dust level, an NIOSH approved disposable dust respirator, properly fitted, should be used.
Skin Contact:	A loose fitting, long sleeved cotton shirt, long cotton pants and gloves are recommended to avoid the potential of skin irritation.
Eye Contact:	Dust may cause stinging, redness or swelling.
Ingestion :	These products are not intended to be ingested (eaten). In the event of accidental ingestion, short term irritation of the gastrointestinal tract (mouth, throat, stomach, small and large intestines) may occur.

HAZARD RATING (National Fire Protection Association)			
HEALTH	1		
FLAMMABILIT			
Y	1		
REACTIVITY	0		
SPECIAL NOTE	-		

C (National Fire Drotaction Accessition)

Legend: 0 - Minimal, 1 - Slight, 2 - Moderate, 3 - Serious, 4 - Severe

# **SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS**

Name	CAS Number	Weight %	OSHA	ACGIH
------	------------	----------	------	-------

				15
Organic Felt Paper	NE	<60	10 mg/m3	mg/m3
Asphalt Flux	8052-42-4	<70	5 fume	5 fume

# NE = Not Established

SECTION 4 - FIRST AID MEASURES			
Eye Contact:	Flush eyes with clean water for 5-15 minutes. DO NOT RUB OR SCRATCH EYES. If irritation persists, contact a physician.		
Skin Contact:	Wash hands with soap and warm water to remove dust and residue. If irritaion occurs/persists, contact a physician.		
Inhalation:	Remove person to fresh, uncontaminated air. Drink clean water to clear throat. Blow nose to clear sinus cavities. If irritation occurs/persists, contact a physician.		
Ingestion :	If product is swallowed, do not induce vomiting. SEEK IMMEDIATE MEDICAL ATTENTION.		
Notes to Physicians:	These products, under normal use, are not expected to produce any chronic health issues. Treatment should be based upon removal of the source of irritation and treatment of symptoms if necessary.		

# **SECTION 5 - FIRE FIGHTING MEASURES**

Suitable Extinguishing:	Water spray, foam, carbon dioxide, dry chemical
Special Hazards:	None

Flash Point:	Not applicale
Note to Fire Fighters:	If involved in fire, employ normal fire fighting procedures to prevent inhalation of smoke and gases. Use of a NIOSH approved self-contained breathing apparatus with full face mask and protective clothing and gloves is recommended.

# **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Personal Precautions:	Not applicable	
Emergency Procedures:	Not applicable	
<b>Environmental Precautions</b>	: No data available	
Clean-up Procedures:	Pick up large pieces. Vacuum dust. Avoid sweeping dry dust. If sweeping is required, use a dust suppressant such as water.	
Waste Disposal:	Comply with state and local regulations for disposal of this product. These wastes are not hazardous as defined by the Resourse Conservation and Recovery Act (40 CFR 261).	

# SECTION 7 - HANDLING AND STORAGE

Handling Procedures:	Comply with all local, state, OSHA, NFPA and EPA requirments. Observe Personal Protection as outlined in Section 8 of this SDS when handling these products.
Storage Procedures:	Material is intended to be stored in a clean and dry area. Material is intended to be stored in an area where it

#### **SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION**

Respiratory Protection:	Though not required under normal use, if exposure limits are exceeded, use a NIOSH approved respirator per its instructions.
Eyes/Face Protection:	Wearing of safety glasses with side shields is recommended.
Skin Protection:	A loose fitting long-sleeved cotton shirt, long cotton pants and gloves are recommended.

#### **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Rolled sheet	Color:	Black
Physical form:	Solid	Odor:	Petroleum asphalt
Boiling Point:	Not applicable	Taste:	Not applicable
Melting Point:	>200 degrees F	pH:	No data
Specific Gravity:	Variable	Viscosity:	Not applicable
Decomposition Temp:	No data	Density:	Not applicable
Water Solubility:	Insoluble	Volatiles:	No data
Solvent Solubility:	No data	VOCs:	Not applicable

#### SECTION 10 - CHEMICAL STABILITY AND REACTIVITY INFORMATION

Stability:	Stable under normal conditions of use
Polymerization:	Will not occur
Decomposition:	Especially due to decomposition by burning, these products may form carbon monoxide, carbon dioxide

	and carbon particles.
Materials to Avoid:	None
Conditions to Avoid:	Excessive heat. Excessive mechanical handling that may generate high dust levels. Keep products away from sparks, ignition sources and open flames.

# SECTION 11 - TOXICOLOGICAL INFORMATION

Acute and Chronic Toxicity	Exposure Limits: Reference: "Guide to Occupational Exposure Values 2000, Compiled by ACGIH <sup>®</sup> "
Acute Effects:	Repeated contact may cause skin irritation due to roughness of product. Dust entering eyes may cause irritation including tear formation, redness, swelling and stinging. If ingested (swallowed), it may cause irritation of the gastrointestinal tract (mouth, throat, stomach and intestines).
Chronic Effects:	Dermatitis (redness, drying and cracking of the skin) may occur in the case of repeated and prolonged skin contact. Silicosis (pulmonary fibrosis or lung scarring) may occur in the case of excessive exposure or repeated exposure to high levels of dust.
Carcinogenicity:	Felt Paper - None Asphalt - CAS Number 8052-42- 4

#### **SECTION 12 - ECOLOGICAL INFORMATION**

No data available for these products. These products are not expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems.

#### **SECTION 13 - DISPOSAL CONSIDERATIONS**

Product Information:	As supplied, the products are not an EPA RCRA hazardous waste according to federal regulations.
Disposal Instructions:	Dispose of material in accordance with local, state and federal regulations.

#### **SECTION 14 - TRANSPORTATION INFORMATION**

This product is not regulated under DOT Dangerous Goods Regulations.

Proper Shipping Name:	Not applicable
Hazard Class:	Not applicable
Packing Group:	Not applicable
Label Statement:	Not applicable
DOT Reportable Quantity:	Not applicable
UN/Identification Number:	Not applicable
Special Precautions:	Not applicable

#### **SECTION 15 - REGULATORY INFORMATION**

US Federal Regulations		
TCSA:	This product contains some components listed on the TSCA 8(b) inventory	
CERCLA:	None	

SARA:					
	Sec 302		None		
	Sec 311/312		Acute Health: Yes	Chronic Health: Yes	
	Sec 313		None		
US State R	egulations				
Asphalt Flux, CAS Number 8052-42-4, appears on the following state hazardous substances lists: CA, MA, MN, NJ, PA, RI.					
California Proposition 65:		This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive effects. Other state regulations may apply. Check individual state requirements.			
International Regulations: Canada DSL/NDSL Inventory:		Not applicable			
WHMIS Sta	atus:		Not controlled		
WHMIS Classification:		None			
SECTION 16 - OTHER INFORMATION					
Date of Cre	eation:	18-Aug-16			
Date of Rev	vision:	9-Jan-24			
Prepared b	ру:	Warrior Roofing Manufacturing			
Disclaimer	:	Reasonable care has been taken in the preparation of			

the information provided in this Safety Data Sheet. The manufacturer makes no warranty, expressed or implied, with repesct to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.