



# WARRIOR<sup>®</sup> ROOFING MANUFACTURING

P. O. BOX 40185 • TUSCALOOSA, AL 35404 • PHONE (205) 553-1734 • FAX (205) 553-1755

193 LEROY ANDERSON ROAD • MONROE, GA 30655 • PHONE (770) 207-0695 • FAX (770) 207-0775

323 DEVELOPMENT AVENUE • CHAMBERSBURG, PA 17201 • PHONE (717) 709-0323 • FAX (717) 709-0027

## SPECIFICATIONS

### # 30 W

In the absence of an industry standard for this product, our #30W asphalt saturated organic felt is manufactured to meet or exceed the following dimensions and specifications:

#### ASTM – D-4869 Type II

Dimensions and specifications of #30 W asphalt felt are:

<b>Width of roll:</b>	<b>36" +/-0.7%</b>
<b>Area:</b>	<b>216 sq. ft.</b>
<b>Net mass of saturated felt:</b>	<b>13.0 lbs./100 sq. ft.</b>
<b>Net mass of saturant:</b>	<b>6.0 lbs./100 sq. ft.</b>
<b>Saturant Weight:</b>	<b>Shall not be less than 1.2 times the weight of the moisture free felt.</b>
<b>Packaging:</b>	<b>The rolls are wrapped securely and the manufacturer's or distributor's name, type and specification markings are evident on the label. UPC bar coding is included on all our labels.</b>

Updated May 2013